

## **CUSTOM**

## DIT UNIVERSAL STRAIGHT COLUMN

610 S. Maumee Street, Tecumseh, MI 49286 Ph: 517-424-0577 www.ididit.com (Standard measurements are shown)

_			
	<u> </u>	0	4" Head
			/ I lead
			11 1/2"
			1
		Wire → Harness	*
Overall Length			
		<b>←</b> 2" <b>→</b>	
,			1 1/2"

To customize your column please download this form & fill in the fields below. Mark the customer drawing if necessary, add any additional comments and sign. Once you are satisfied, save the filled out form and email it to us at sales@ididit.com.

Reposition Wire Harness:	″ from Top of Column			
Overall wire harness position is med	asured from top of head to top of wire harne	ess		
location. Standard is 11-1/2". Max				
Rotation of vvire marness:  Rotation starts at 12 o'clock from se	: o'clock (per half ha	ourj		
	2" (Steel) 1 3/4"(Aluminu	m)		
Shaft Length: " Out of tube (Max 8")				
•	$48_{\text{aluminum}}^{\text{(standard or aluminum)}}$ 3/4"DD 1" DD $_{\text{aluminum}}^{\text{(standard or aluminum)}}$	3/4″ 36		
Overall Length: (from top of h	nead to the bottom of shaft)			
Column Finish (check one):	Paintable Steel Chrome B	lack		
	Brushed Aluminum Polished A	Aluminum		
Vehicle:	Year:			
Additional Comments:				
Name:				
Phone: Er	mail:			
	ee to recognize this as my legal signatur re supplied is correct and I assume responded made on this form.			
Signature:				
Date://				